



Technical Data Sheet-DPH

DPH-F17 Height 17mm

COMPONENTS

The DPH-F17 is composed of one piece

CHARACTERISTICS

Top: \varnothing 145 mm, 165 cm²

Base: \varnothing 170 mm, 227 cm²

Weight: 0,094 kg

Non Adjustable

With addition of a 0 to 5% DPH-PH5 slope corrector,
adjustable in height of 26 mm

MATERIAL

Copolymer polypropylene (CPP)



Composition: +/- 80% first grade pre-selected recycled
PPC, and +/- 20% Talc + Masterbatch black

Designed and manufactured in Europe

Use of recycled materials exclusively of EU origin

Resistant to weathering, sea salts, algae and a wide
range
of chemicals

Temperature range: -30 °C to +80 °C



PACKAGING

Pieces per carton: 144 pcs

Carton weight: 14,39 Kg

Carton dimension: 520 x 350 x 410 mm

Cartons per pallet: 35 pcs

Pieces per pallet: 5 040 pcs

Pallet dimensions: 100 x 120 x 220 cm

APPLICATIONS

Buzon pedestals can be used for a wide range of outdoor applications, such as terraces, pool decks and water features, in landscape areas and on rooftops... Finishing materials can be freely specified by the designer. Accessories are available for applications with various outdoor finishes, such as granite stone pavers, composite / timber decking, ceramic tiles and fibreglass or metal grating panels. Buzon pedestals can be installed on a wide range of solid and stable substrates, such as concrete slabs, cement screeds, waterproof membranes, insulation panels.

Spacer Tabs



Thickness: 3 and 4,5mm



Thickness: 2, 4,5, 6, 8 and 10mm

Batten Holder



Thickness: 4 mm
Joist max.: 65 mm

Shims



U-E10 (T = 1mm)
U-E20 (T = 2mm)

COMPRESSION TEST*

Performed on the full (1/1), half (1/2) and quarter (1/4) surface of the head (1kN= 100 kg= 224,8 lbf)

Position	Height (mm)	Yield strength** (kN)	Yield strength (lbf)	Breaking load (kN)	Breaking load (lbf)
1/1	17	32,25 (3 225 kg)	7 250	48,20 (4 820 kg)	10 835
1/2	17	20 (200 kg)	4 496	32,20 (3 220 kg)	7 193
1/4	17	10 (10 kg)	2 248	18,60 (1 860 kg)	4 181

* Tests carried out by SIRRIS

** The yield point is the stress from which a material stops deforming in an elastic, reversible manner and thus begins to irreversibly deform (ISO472 :2013)

SAFETY INSTRUCTIONS

Buzon pedestals are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.



Buzon has a policy of continuous improvement and reserves the right to modify, revise or change the above specifications without notice. This brochure is for descriptive purpose only and is based on the product as on the date of publication of this information.

© Copyright Buzon Pedestal International SA Buzon DPH® is a registered trade mark of Buzon Pedestal International SA.